



Office Products Group

**MATERIAL SAFETY DATA SHEET****MSDS # 63701****Section One: Identification**

Sanford, L.P.  
2707 Butterfield Road  
Oak Brook, IL 60523 USA  
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: Uni-Paint Px-21 Fine and Px-20 Medium Marker

Colors: White, Yellow, Orange, Green, Lt Blue, Blue, Violet, Pink, Red, Black, Gold, Silver

Writing Instrument Manufacturers Association (WIMA) certified. Conforms to ASTM D-4236. These markers and the inks contained within have been examined by the WIMA Board Certified Toxicologist in a program of toxicological evaluation to assure they are in compliance with Federal Hazardous Substances Act (FHSA), Labeling of Hazardous Art Materials Act (LHAMA), and ASTM D-4236.

**Section Two: Hazard Identification**

Acute hazard: At high concentration, dizziness, drowsiness, and unconsciousness may occur. CAUTION: Contains xylene. Harmful or fatal if swallowed. KEEP OUT OF REACH OF CHILDREN. Direct contact may cause skin or eye irritation.

\*\*WARNING: This product contains a chemical known to the State of California to cause cancer.

**Section Three: Composition**

Xylene (1330-20-7), pigments, resin, dyes

**Section Four: First Aid Measures**

Inhalation: Move person to fresh air if symptoms persist, seek medical attention.

Skin Contact: Wash with soap and water.

Eye Contact: Flush with water. If irritation persists, seek medical attention .

Ingestion: Contact physician immediately! DO NOT induce vomiting. Do Not give anything by mouth.

**Section Five: Fire Fighting Measures**Flash Point: 27-32C<sub>xylene</sub> (CC)

Flammability Limits (% by volume): Lower: 1.1% Upper: 6.4%

Extinguishing Media: Dry chemical, carbon dioxide, regular foam

Special Fire Fighting Measures: For large fires, use foam or flood with fine water spray.

Unusual Fire and Explosion Hazards: Avoid inhalation of material or combustion by-products. Stay upwind.

**Section Six: Accidental Release Measures**

In Case of Spill or Accidental Release: Treat as flammable solvent. Use adequate ventilation.

**Section Seven: Handling and Storage**

Handling: Keep marker capped when not in use. Avoid unnecessary contact with skin. Use in well ventilated area.

Storage: Keep away from Heat and open flame. KEEP OUT OF REACH OF CHILDREN.

**Section Eight: Exposure Controls and Personal Protection**

Eye Protection: None under normal use conditions.

Clothing: None under normal use conditions.

Respirator: None under normal use conditions.

Ventilation: Use in a well ventilated area.

**Section Nine: Physical and Chemical Properties**

**For ink unless otherwise specified:**

Boiling Point: 138.5C (xylene)  
 Specific Gravity: 1.25 - 1.32  
 Vapor Pressure: 6.72 mm Hg at 21C  
 Solubility in Water: Insoluble  
 Evaporation Rate: Not available  
 Appearance/Odor: Colored ink; xylene odor

**Section Ten: Stability and Reactivity**

Stability: Stable  
 Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition.  
 Chemical Incompatibility: Strong oxidizers  
 Hazardous Decomposition: Oxides of carbon in fire situation.  
 Hazardous Polymerization: Will not occur.

**Section Eleven: Toxicological Information**

See Section Two: Hazard Identification for any hazards

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations.

**Section Fourteen: Transport Information**

DOT: ORM-D Consumer Commodity  
 IATA: Consumer Commodity, 9, ID8000, packing instruction Y963  
 IMO: Not determined

**Section Fifteen: Regulatory Information**

TSCA: The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

**\*\*WARNING:** This product contains a chemical known to the State of California to cause cancer\*\*

**Section Sixteen: Other Information**

HMIS Code	
Health	2
Flammability	3
Reactivity	0
Personal Protection	N/A

NewellRubbermaid, Inc (Sanford L.P) has been advised by Counsel that the OSHA Hazard Communication Standard and the Health Canada Workplace Hazardous Materials Information Standard do not apply to the product described in this Material Safety Data Sheet. The reasons for the exemptions are contained in 29 CFR 1910.1200(b)(6)(ix) as amended Sept 14, 2009 per the Code of Federal Regulations and also Canadian Hazardous Products Act part 12 section (f) as amended June 1, 2009. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by nor is this MSDS meant to comply with all requirements of the hazard communication standards.

**0=Minimal / 4 = Severe**