

Page 1 of 4 Carbon Zinc Batteries March 2015

PRODUCT SAFETY DATA SHEET

PRODUCT NAME: Eveready Battery

Type No.:

Volts:

TRADE NAMES: CLASSIC; SUPER HEAVY DUTY; INDUSTRIAL; HERCULES

Approximate Weight:

CHEMICAL SYSTEM: Carbon Zinc

Designed for Recharge: No

Energizer has prepared copyrighted Product Safety Datasheets to provide information on the different Eveready/Energizer battery systems. Batteries are articles as defined under the GHS and exempt from GHS classification criteria (Section 1.3.2.1.1 of the GHS). The information and recommendations set forth herein are made in good faith, for information only, and are believed to be accurate as of the date of preparation. However, ENERGIZER BATTERY MANUFACTURING, INC. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM REFERENCE ON IT.

SECTION 1 - MANUFACTURER INFORMATION

Energizer Battery Manufacturing, Inc. 25225 Detroit Rd.

Westlake, OH 44145

Telephone Number for Information: 800-383-7323 (USA / CANADA)

Date Prepared: March 2015

SECTION 2 - HAZARDS IDENTIFICATION

GHS classification: N/A

Signal Word: N/A

Hazard Classification: N/A

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

Inhalation: Contents of an open battery can cause respiratory irritation.

Skin Contact: Contents of an open battery can cause skin irritation and/or chemical burns. **Eye Contact:** Contents of an open battery can cause severe irritation and chemical burns.

SECTION 3 - INGREDIENTS

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Acetylene Black (CAS# 1333-86-4)	3.5 mg/m³ TWA (as carbon black)	3.5 mg/m³ TWA (as carbon black)	3-7
Ammonium Chloride (CAS# 12125-02-9)	None established	10 mg/m³ TWA (fume) 20 mg/m³ STEL (fume)	0-10
Manganese Dioxide (CAS# 1313-13-9)	5 mg/m³ CEILING (as Mn)	0.2 mg/m³ TWA (as Mn)	15-31
Zinc (CAS# 7440-66-6)	15 mg/m³ TWA PNOR* (total dust) 5 mg/m³ TWA PNOR* (respirable fraction)	10 mg/m³ TWA PNOC** (inhalable particulate) 3 mg/m³ TWA PNOC** (respirable particulate)	7-42



Page 2 of 4 Carbon Zinc Batteries March 2015

Zinc Chloride (CAS# 7646-85-7)	1 mg/m³ TWA (fume)	1 mg/m³ TWA (fume) 2 mg/m³ STEL (fume)	2-10
Non-Hazardous Components Steel	None established	None established	23-28
(Iron CAS #65997-19-5) Water, Paper, Plastic and Other	Non established	Non established	Balance

^{*} PNOR: Particulates not otherwise regulated

SECTION 4 - FIRST AID MEASURES

Ingestion: Do not induce vomiting or give food or drink. Seek medical attention immediately. CALL NATIONAL BATTERY INGESTION HOTLINE for advice and follow-up (202-625-3333) collect day or night.

Inhalation: Provide fresh air and seek medical attention.

Skin Contact: Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements: Room ventilation may be required in areas where there are open or leaking batteries.

Eye Protection: Wear safety glasses with side shields if handling an open or leaking battery.

Gloves: Use neoprene or natural rubber gloves if handling an open or leaking battery.

Battery materials should be collected in a leak-proof container.

SECTION 7 - HANDLING AND STORAGE

Storage: Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.

Mechanical Containment: If potting or sealing the battery in an airtight or watertight container is required, consult your Energizer Battery Manufacturing, Inc. representative for precautionary suggestions. Batteries normally evolve hydrogen which, when combined with oxygen from the air, can produce a combustible or explosive mixture unless vented. If such a mixture is present, short circuits, high temperature, or static sparks can cause an ignition.

Do not obstruct safety release vents on batteries. Encapsulation (potting) of batteries will not allow cell venting and can cause high pressure rupture.

Handling: Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, consult your Energizer Battery Manufacturing, Inc. representative for proper precautions to prevent seal damage or short circuit.

Charging: This battery is manufactured in a charged state. It is not designed for recharging. Recharging can cause battery leakage or, in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards.

Labeling: If the Eveready Battery label or package warnings are not visible, it is important to provide a package and/or device label stating:

^{**}PNOC: Particulates not otherwise classified



Page 3 of 4 Carbon Zinc Batteries March 2015

WARNING: do not install backwards, charge, put in fire, or mix with other battery types. May explode or leak causing injury. **Replace all batteries at the same time.**

Where accidental ingestion of small batteries is possible, the label should include:

Keep away from small children. If swallowed, promptly see doctor; have doctor phone (202) 625-3333 collect.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions. **Gloves:** Not necessary under normal conditions.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid object
Upper Explosive Limits:	Not applicable for an Article
Lower Explosive Limits	Not applicable for an Article
Odor	No odor
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Odor Threshold	No oder
Vapor Density (Air = 1)	Not applicable for an Article
рН	Not applicable for an Article
Density (g/cm³)	2.0 – 3.0
Melting point/Freezing Point	Not applicable for an Article
Solubility in Water (% by weight)	Not applicable for an Article
Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Flash Point	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Flammability	Not applicable for an Article
Partition Coefficient	Not applicable for an Article
Auto-ignition Temperature	Not applicable for an Article
Decomposition Temperature	Not applicable for an Article
Viscosity	Not applicable for an Article



Page 4 of 4 Carbon Zinc Batteries March 2015

SECTION 10 - STABILITY AND REACTIVITY

Carbon zinc batteries do not meet any of the criteria established in 40 CFR 261.2 for reactivity.

SECTION 11 – TOXICOLOGICAL INFORMATION

Under normal conditions of use, carbon zinc batteries are non-toxic.

SECTION 12 - ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state and local regulations. Appropriate disposal technologies include incineration and land filling.

SECTION 14 – TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer alkaline batteries has been designed to be compliant with these regulatory concerns.

Carbon zinc batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	Not regulated
IMDG	Not regulated
UN	Not regulated
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	Not regulated

All Energizer or Eveready carbon zinc batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

SECTION 15 - REGULATORY INFORMATION

Batteries marketed by Energizer Battery Manufacturing, Inc. are not classified as dangerous goods by the US Department of Transportation or the major international regulatory bodies and are therefore not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

SECTION 16 - OTHER INFORMATION	

None.

©2015 Energizer



Office Products Group

MATERIAL SAFETY DATA SHEET

MSDS#

3000

Section One:

Identification

Newell Rubbermaid, Inc. (Sanford L.P.) 2707 Butterfield Road Oak Brook, IL 60523 USA 800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name:

Sharpie Fine Point Marker, Sharpie Ultra Fine Point Marker, Sharpie Extra Fine Marker, Sharpie Chisel Tip Marker, Sharpie Twin Tip Marker, Super Sharpie Marker, Super Sharpie Twin Tip Marker, Sharpie Mini Fine Point Marker, Sharpie Micro Marker, Sharpie Grip Marker, Sharpie Retractable Fine Point Marker, Sharpie Magnum Marker, Sharpie King Size Marker, Sharpie Liquid Tip Marker Sharpie Premium, Sharpie CD Marker, Sharpie Pro, Sharpie Pro King Size, Sharpie Pro Magnum, Sharpie Aluminum Barrel, Sharpie Brush Tip Marker, Eslerbrook by Sharpie

Colors:

All Colors

NewellRubbermaid, Inc (Sanford L.P.) is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is tabeled with the AP Non Toxic Seal. Products bearing the AP Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute Toxicology Advisory Board, to contain no materials in sufficient quantities to be toxic or Injurious to humans, or to cause acute toxicity or chronic health problems.

Section Two:

Hazard Identification

Not Hazardous under normal use conditions. Not for use on skin. Do not ingest. Contact with eyes may cause irritation.

Section Three:

Composition

Butanol (71-36-3), Propanol (71-23-8), Diacetone Alcohol (123-42-2), Ethanol (64-17-5), pigments, dyes, additives

Section Four:

First Aid Measures

Inhalation:

Remove source of irritation, if symptoms persist seek medical attention.

Wash with soap and water. If irritation persists seek medical attention.

Skin Contact: Eye Contact:

Rinse eyes with water, if irritation persists seek medical attention.

Ingestion

If symptoms occur seek medical attention

Section Five:

Fire Fighting Measures

Flash Point:

Extinguishing Media:

As appropriate for surrounding area

Special Fire Fighting Measures:

N/A

Hazardous combustion products;

. . .

Section Six:

Accidental Release Measures

In Case of Spill or Accidental Release:

Wipe up with absorbent material.

Section Seven:

Handling and Storage

Handling:

Do not shake marker.

Storage:

Keep cap on marker when not in use.

Exposure Controls and Personal Protection

Eye Protection:

None under normal use conditions.

None under normal use conditions.

Clothing: Respirator:

None under normal use conditions.



Office Products Group

MATERIAL SAFETY DATA SHEET

MSDS#

3000

		MODO #	3000
Castion Nine	Division and Observed Division		
Section Nine:	Physical and Chemical Properties		
Boiling Point.	N/A		
Specific Gravity.	N/A		
Vapor Pressure:	N/A		
Solubility in Water:	N/A		
Evaporation Rate:	NA		
Appearance/Odor:	Marker/Alcohol (ink)		
Section Ten:	Stability and Reactivity		
Stability:	N/A	· ·· -	
Conditions to Avoid:	Avoid exposure to heat, flame or other sources of ignition.		
Chemical Incompatible	tity: N/A		
Hazardous Polymeriz	ation: N/A		
Section Eleven:	Toxicological Information		
See Section Two Ha	zard Identification for any hazards		
Section Twelve:	Ecological Information		
Not available			
Section Thirteen:	Disposal Considerations		
Dispose of in accorda	nce with all Federal, State, and Local Regulations,		
Section Fourteen:	Transport Information		
DOT:	Not available		
IATA.	Not available		
IMO:	Not available		
Section Fifteen:	Regulatory Information		
United States:	All components in this product are listed on or exempt from reporting under (TSCA).	the Federal Toxic Substances Control	Act

Section	Six	teen:	

Other Information

HMIS Code

Health N/A
Flammability N/A
Reactivity N/A

Personal Protection N/A

0=MinImal / 4 = Severo

NewellRubbermaid, Inc has been advised by Counsel that the OSHA Hazard Communication Standard and the Health Canada Workplace Hazardous Materials Information Standard do not apply to the Sanford Product described in this Material Safety Data Sheet. The reasons for the exemptions are contained in 29 CFR 1910.1200(b)(6)(ix) as amended Sept 14, 2009 per the Code of Federal Regulations and also Canadian Hazardous Products Act part 12 section (f) as amended June 1, 2009. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by nor is this MSDS meant to comply with all requirements of the hazard communication standards.



Hazard Communication Compliance Declaration

Newell-Rubbermaid (NWL) writing instruments comply with U.S. OSHA GHS Hazard Communication Standard of 29 CFR section 1910.1200 (OSHA HazCom 2012) by virtue of exemption as 'articles' and as 'consumer products' per 29 CFR section 1910.1200(b)(6)(v) and (ix). Therefore, GHS Safety Data Sheets are not required for our writing instruments.

An 'article' is defined in Section 1910.1200(c) "as a manufactured item other than a fluid or particle:

- Which is formed to a specific shape or design during manufacture;
- Which has end use function(s) dependent in whole or in part on its shape or design during end use; and
- Which, under normal conditions of use, does not release other than very small (minute or trace) amounts of a hazardous chemical and does not pose a physical hazard or health risk to employees."

The 'consumer product' exemption in 29 C.F.R. section 1910.1200(b)(6)(ix) states that:

• Any consumer product or hazardous substance, as those terms are defined in the Consumer Product Safety Act (15 U.S.C. 2051 et seq.) and Federal Hazardous Substances Act (15 U.S.C. 1261 et seq.) respectively, where the employer can show that it is used in the workplace for the purpose intended by the chemical manufacturer or importer of the product, and the use results in a duration and frequency of exposure which is not greater than the range of exposures that could reasonably be experienced by consumers when used for the purpose intended.

OSHA has consistently taken the position, in various rulemaking documents and interpretation letters, "most office products (such as pens, pencils, adhesive tape) to be exempt under the provisions of the rule, either as articles or as consumer products." Markers also fall into these exempted categories. This position is cited currently on <u>OSHA's website</u> in a letter from OSHA Assistant Secretary John A. Pendergrass to U.S. Congressman Jim Bunning. These examples are cited again in OSHA's FAQs on the <u>Hazard Communication Standard</u> which further reinforces that Newell-Rubbermaid writing products are exempt from Hazard Communication requirements, specifically GHS Safety Data Sheet documentation.

A non-exhaustive list is provided below of Newell-Rubbermaid writing instruments that qualify as 'articles' and 'consumer products' that are exempt from GHS Safety Data Sheet requirements:

- Prismacolor Premier Colored Pencils and Sharpeners
- Prismacolor Nupastels and Art Stix and Erasers
- Sharpie Permanent Markers
- Sharpie Pens
- Sharpie Highlighters (Clearview, Accent, etc)
- Paper Mate Pens (Inkloy, FlexGrip, Replay, etc)
- Paper Mate Mechanical Pencils
- Paper Mate Flair Pens
- Paper Mate Pearl Erasers
- Paper Mate Replay Premium Erasable Pens

- Expo Dry Erase Markers
- Expo Whiteboard Cleaner Wipes
- Expo Learning Boards
- Liquid Paper Correction Pens
- Liquid Paper Dryline Correction Tape
- Parker Fountain Pens
- Waterman Fountain Pens
- Rotring Tikky Ballpoint Pens
- Woodcase Pencils (Mongol, Mirado, etc)
- uni-ball pens

3500 Lacey Road | Downers Grove, IL | Phone +1 (630)-829-2500 | www.newellrubbermaid.com

Shanpie.

IRWIN.

Goody





Calphalon (S)

HATERMAN

LENOX4

Paper Mate

LEVOLOR







Aprica.



A Neweil Rubbermaid Company

MATERIAL SAFETY DATA SHEET

MSDS#

061108

Section One: Identification

Sanford, L.P. 2707 Butterfield Road Oak Brook, IL 60523 USA 800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name:

Vis-à-Vis Wet-Erase Transparency Marker

Colors:

Black, Red, Blue, Green, Yellow, Orange, Brown, Purple

Sanford is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the AP Non Toxic Seal. Products bearing the AP Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute Toxicology Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans, or to cause acute toxicity or chronic health problems.

Section Two:

Hazard Identification

This product is considered safe under normal use conditions.

Section Three:

Composition

Water, propylene glycol (57-55-6), dyes, resins, additives

Section Four:

First Aid Measures

Inhalation:

This product is considered safe under normal use conditions.

Skin Contact:

This product is considered safe under normal use conditions.

This product is considered safe under normal use conditions.

Eye Contact:

This product is considered safe under normal use conditions.

Ingestion:

Fire Fighting Measures

Section Five: Flash Point:

Not flammable

Flammability Limits (% by volume):

Not explosive

Upper: Not explosive

Extinguishing Media:

As appropriate for surrounding area.

Special Fire Fighting Measures:

None

None

Lower:

Unusual Fire and Explosion Hazards:

Section Six:

Accidental Release Measures

In Case of Spill or Accidental Release:

Wipe up with absorbent material.

Section Seven:

Handling and Storage

Handling:

Do not shake pen.

Storage:

Keep cap on pen when not in use.

Section Eight:

Exposure Controls and Personal Protection

Eye Protection:

None under normal conditions.

Clothing:

None under normal conditions.

Respirator:

None under normal conditions.

Ventilation:

None under normal conditions.

June 6, 2008

Page 1 of 2



A Neivell Rubbermaid Company

MATERIAL SAFETY DATA SHEET

MSDS#

061108

Section Nine:

Physical and Chemical Properties

For Ink unless otherwise specified:

Boiling Point:

Approximately 212F

Specific Gravity:

-1

Vapor Pressure:

Not determined

Solubility in Water:

Soluble

Evaporation Rate:

Not determined

Appearance/Odor:

Colored liquid; essentially odorless

Section Ten:

Stability and Reactivity

Stability:

Stable

Conditions to Avoid:

None known

Chemical Incompatibility:

Nane known

Hazardous Decomposition:

None known

Hazardous Polymerization:

Will not occur

Section Eleven:

Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve:

Ecological Information

Not available

Section Thirteen:

Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations

Section Fourteen:

Transport Information

DOT:

Not regulated as a hazardous material by DOT, IMO, or IATA

IATA:

IMO:

Section Fifteen:

Regulatory Information

TSCA:

The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen:

Other Information

HMIS Code

Health

N/A

Flammability

N/A

Reactivity

N/A N/A

Personal Protection

Sanford has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2006 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.

0=Minimal / 4 = Severe

June 6, 2008

Page 2 of 2



Hazard Communication Compliance Declaration

Newell-Rubbermaid (NWL) writing instruments comply with U.S. OSHA GHS Hazard Communication Standard of 29 CFR section 1910.1200 (OSHA HazCom 2012) by virtue of exemption as 'articles' and as 'consumer products' per 29 CFR section 1910.1200(b)(6)(v) and (ix). Therefore, GHS Safety Data Sheets are not required for our writing instruments.

An 'article' is defined in Section 1910.1200(c) "as a manufactured item other than a fluid or particle:

- Which is formed to a specific shape or design during manufacture;
- Which has end use function(s) dependent in whole or in part on its shape or design during end use; and
- Which, under normal conditions of use, does not release other than very small (minute or trace) amounts of a hazardous chemical and does not pose a physical hazard or health risk to employees."

The 'consumer product' exemption in 29 C.F.R. section 1910.1200(b)(6)(ix) states that:

• Any consumer product or hazardous substance, as those terms are defined in the Consumer Product Safety Act (15 U.S.C. 2051 et seq.) and Federal Hazardous Substances Act (15 U.S.C. 1261 et seq.) respectively, where the employer can show that it is used in the workplace for the purpose intended by the chemical manufacturer or importer of the product, and the use results in a duration and frequency of exposure which is not greater than the range of exposures that could reasonably be experienced by consumers when used for the purpose intended.

OSHA has consistently taken the position, in various rulemaking documents and interpretation letters, "most office products (such as pens, pencils, adhesive tape) to be exempt under the provisions of the rule, either as articles or as consumer products." Markers also fall into these exempted categories. This position is cited currently on OSHA's website in a letter from OSHA Assistant Secretary John A. Pendergrass to U.S. Congressman Jim Bunning. These examples are cited again in OSHA's FAQs on the Hazard Communication Standard which further reinforces that Newell-Rubbermaid writing products are exempt from Hazard Communication requirements, specifically GHS Safety Data Sheet documentation.

A non-exhaustive list is provided below of Newell-Rubbermaid writing instruments that qualify as 'articles' and 'consumer products' that are exempt from GHS Safety Data Sheet requirements:

- Prismacolor Premier Colored Pencils and Sharpeners
- Prismacolor Nupastels and Art Stix and Erasers
- Sharpie Permanent Markers
- Sharpie Pens
- Sharpie Highlighters (Clearview, Accent, etc)
- Paper Mate Pens (Inkloy, FlexGrip, Replay, etc)
- Paper Mate Mechanical Pencils
- Paper Mate Flair Pens
- Paper Mate Pearl Erasers
- Paper Mate Replay Premium Erasable Pens

- Expo Dry Erase Markers
- Expo Whiteboard Cleaner Wipes
- Expo Learning Boards
- Liquid Paper Correction Pens
- Liquid Paper Dryline Correction Tape
- Parker Fountain Pens
- Waterman Fountain Pens
- Rotring Tikky Ballpoint Pens
- Woodcase Pencils (Mongol, Mirado, etc)
- uni-ball pens

3500 Lacey Road | Downers Grove, It. | Phone +1 (630)-829-2500 | www.newellrubbermaid.com

Sharpie.

IRWIN.









WATERMAN

LENOX 6.

Paper Mate

LEVOLOR









Page 1 of 4 Alkaline Batteries March 2015

PRODUCT SAFETY DATA SHEET

PRODUCT NAME: Eveready / Energizer Battery

Type No.:

Volts:

TRADE NAMES: ENERGIZER, ENERGIZER e2, INDUSTRIAL ZMA, HERCULES,

EVEREADY, WONDER

Approximate Weight:

CHEMICAL SYSTEM: Alkaline Manganese Dioxide-Zinc

Designed for Recharge: No

Energizer has prepared copyrighted Product Safety Datasheets to provide information on the different Eveready/Energizer battery systems. Batteries are articles as defined under the GHS and exempt from GHS classification criteria (Section 1.3.2.1.1 of the GHS). The information and recommendations set forth herein are made in good faith, for information only, and are believed to be accurate as of the date of preparation. However, ENERGIZER BATTERY MANUFACTURING, INC. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM REFERENCE ON IT.

SECTION 1 - MANUFACTURER INFORMATION

Energizer Battery Manufacturing, Inc.

25225 Detroit Rd. Westlake, OH 44145 Telephone Number for Information: 800-383-7323 (USA / CANADA)

Date Prepared: March 2015

SECTION 2 - HAZARDS IDENTIFICATION

GHS classification: N/A

Signal Word: N/A

Hazard Classification: N/A

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

Inhalation: Contents of an open battery can cause respiratory irritation.

Skin Contact: Contents of an open battery can cause skin irritation and/or chemical burns. Eye Contact: Contents of an open battery can cause severe irritation and chemical burns.

SECTION 3 - INGREDIENTS

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Graphite (CAS# 7782-42-5)	15 mg/m³ TWA (total dust) 5 mg/m³ TWA (respirable fraction)	2 mg/m³ TWA (respirable fraction)	2-6
Manganese Dioxide (CAS# 1313-13-9)	5 mg/m³ Ceiling (as Mn)	0.2 mg/m³ TWA (as Mn)	30-45
Potassium Hydroxide (CAS# 1310-58-3)	None established	2 mg/m³ Ceiling	4-8
Zinc (CAS# 7440-66-6)	15 mg/m³ TWA PNOR* (total dust) 5 mg/m³ TWA PNOR* (respirable fraction)	10 mg/m³ TWA PNOC** (inhalable particulate) 3 mg/m³ TWA PNOC** (respirable particulate)	12-25



Page 2 of 4 Alkaline Batteries March 2015

Non-Hazardous Components			
Steel	None established	None established	18-22
(iron CAS# 65997-19-5			
Water, Paper, Plastic and Other	None established	None established	Balance

^{*} PNOR: Particulates not otherwise regulated

**PNOC: Particulates not otherwise classified

SECTION 4 - FIRST AID MEASURES

Ingestion: Do not induce vomiting or give food or drink. Seek medical attention immediately. CALL NATIONAL BATTERY INGESTION HOTLINE for advice and follow-up (202-625-3333) collect day or night.

Inhalation: Provide fresh air and seek medical attention.

Skin Contact: Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements: Room ventilation may be required in areas where there are open or leaking batteries.

Eye Protection: Wear safety glasses with side shields if handling an open or leaking battery.

Gloves: Use neoprene or natural rubber gloves if handling an open or leaking battery.

Battery materials should be collected in a leak-proof container.

SECTION 7 - HANDLING AND STORAGE

Storage: Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.

Mechanical Containment: If potting or sealing the battery in an airtight or watertight container is required, consult your Energizer Battery Manufacturing, Inc. representative for precautionary suggestions. Batteries normally evolve hydrogen which, when combined with oxygen from the air, can produce a combustible or explosive mixture unless vented. If such a mixture is present, short circuits, high temperature, or static sparks can cause an ignition.

Do not obstruct safety release vents on batteries. Encapsulation (potting) of batteries will not allow cell venting and can cause high pressure rupture.

Handling: Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, consult your Energizer Battery Manufacturing, Inc. representative for proper precautions to prevent seal damage or short circuit.

Charging: This battery is manufactured in a charged state. It is not designed for recharging. Recharging can cause battery leakage or, in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards.

Labeling: If the Eveready / Energizer Battery label or package warnings are not visible, it is important to provide a package and/or device label stating:

WARNING: do not install backwards, charge, put in fire, or mix with other battery types. May explode or leak causing injury. **Replace all batteries at the same time.**

Where accidental ingestion of small batteries is possible, the label should include:

Keep away from small children. If swallowed, promptly see doctor; have doctor phone (202) 625-3333 collect.



Page 3 of 4 Alkaline Batteries March 2015

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions.

Gloves: Not necessary under normal conditions.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid object
Upper Explosive Limits:	Not applicable for an Article
Lower Explosive Limits	Not applicable for an Article
Odor	No odor
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Odor Threshold	No odor
Vapor Density (Air = 1)	Not applicable for an Article
рН	Not applicable for an Article
Density (g/cm³)	2.0 - 3.0
Melting point/Freezing Point	Not applicable for an Article
Solubility in Water (% by weight)	Not applicable for an Article
Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Flash Point	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Flammability	Not applicable for an Article
Partition Coefficient	Not applicable for an Article
Auto-ignition Temperature	Not applicable for an Article
Decomposition Temperature	Not applicable for an Article
Viscosity	Not applicable for an Article

SECTION 10 - STABILITY AND REACTIVITY

Alkaline batteries do not meet any of the criteria established in 40 CFR 261.2 for reactivity.



Page 4 of 4 Alkaline Batteries March 2015

SECTION 11 - TOXICOLOGICAL INFORMATION

Under normal conditions of use, alkaline batteries are non-toxic.

SECTION 12 – ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state and local regulations. Appropriate disposal technologies include incineration and land filling.

SECTION 14 -- TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer alkaline batteries has been designed to be compliant with these regulatory concerns.

Alkaline batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	Not regulated
IMDG	Not regulated
UN	Not regulated
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	Not regulated

All Energizer alkaline batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

SECTION 15 - REGULATORY INFORMATION

Batteries marketed by Energizer Battery Manufacturing, Inc. are not classified as dangerous goods by the US Department of Transportation or the major international regulatory bodies and are therefore not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

SECTION 16 - OTHER INFORMATION

None.